




712 Form

• Hardcopy – on file with MORS office

Report Documentation Page					Form Approved OMB No. 0704-0188	
maintaining the data needed, and c including suggestions for reducing	lection of information is estimated to completing and reviewing the collecti this burden, to Washington Headquuld be aware that notwithstanding an OMB control number.	ion of information. Send comments arters Services, Directorate for Infor	regarding this burden estimate of mation Operations and Reports	or any other aspect of the 1215 Jefferson Davis I	is collection of information, Highway, Suite 1204, Arlington	
1. REPORT DATE 14 JUN 2005		2. REPORT TYPE N/A		3. DATES COVE	RED	
4. TITLE AND SUBTITLE			5a. CONTRACT NUMBER			
SUN-TZU: Proposal for an agent based battle staff planning tool foranalysis of situation awareness data anomalies				5b. GRANT NUMBER		
				5c. PROGRAM ELEMENT NUMBER		
6. AUTHOR(S)				5d. PROJECT NUMBER		
					5e. TASK NUMBER	
					5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) US Army Research LaboratoryAberdeen Proving Ground, MD 21005				8. PERFORMING ORGANIZATION REPORT NUMBER		
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)		
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)		
12. DISTRIBUTION/AVAII Approved for publ	LABILITY STATEMENT ic release, distributi	on unlimited				
	otes 46, Military Operat The original docume		• • •	3rd) Held in	West Point, NY on	
14. ABSTRACT						
15. SUBJECT TERMS						
16. SECURITY CLASSIFIC	17. LIMITATION OF	18. NUMBER	19a. NAME OF			
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified	ABSTRACT UU	OF PAGES 34	RESPONSIBLE PERSON	

Form Approved OMB No. 0704-0188





John Brand Devin Burns Ann Brodeen Richard Kaste

US Army Research Laboratory Aberdeen Proving Ground, MD 21005

Military Operations Research Society Symposium
June 2005
US Military Academy
West Point, NY

Approved for public release-distribution unlimited



What is it?



- Sun-Tzu is a concept for an agent based situational awareness (SA) data base tool intended to find and highlight inconsistencies in the battle SA picture
- The goal is to find inconsistencies that might cue the existence of a deception story
- It is bottom-up, not top-down
- Sources of inconsistency other than deception might be tactically *much more* valuable:
 - incomplete detection—not sensing things that are there
 - mistaken detection or interpretation—wrong identification of sensed element
 - ➤ false detection—seeing what isn't there
 - > mistaken interpretation—wrong picture of reality



Assumptions



- There is a lot of information available—too sparse and you are doomed anyway (Imperial Japan after 1941)
- The information is reasonably correct—too wrong and you are doomed anyway (Nazis after ~1940)
- Basic premise for countering—or implementing—deception with templates is that no deception story can be complete if examined closely enough
- Enemy deceptions *must* be included in set of templates
- Deception may be local or global—due to small unit commander initiative or centrally planned and executed—these will differ in techniques, resources
- Watch out for too good to be true
- This is not RAID—more on that later



Applications



- This analysis cues incongruities or anomalies in the Situation Awareness data base—
- One kind of incongruity or anomaly may underlie an enemy deception effort
- Others may be due to
 - > mis-identifications,
 - > non-detections,
 - > false detections,
 - > mis-interpretations
- At the *tactical* level these are far more likely, and may be *far more* valuable than warning of possible deception per se



Basic thesis



"The possibility of detecting deception... is inherent in the effort to deceive. Every deception operation necessarily leaves at least two clues:

incongruities about what is hidden; and incongruities about what is displayed in (its) stead.

The analyst requires only the appropriate sensors and mindset (cognitive hypotheses) to detect and understand the meaning of these clues. (Whaley-Busby p. 191)."*

*From tutorial, Integrating Methods and Tools to Counter Denial and Deception, Ed Waltz, International Conference on Intelligence Analysis, 2 May 2005, courtesy Frank Stech, MITRE, used with permission.

>>The trick is how to find the clues.



How to do it?



- Basic tool is the template
- Evidence from the study of decision making indicates that, in situations with incomplete data and under time pressures, a high proportion (perhaps 96%*) of decisions are based on recognizing and applying patterns
 - Learned patterns are used to diagnose or recognize situations
 - > Learned patterns are used to implement solutions
 - These patterns are doctrine, tactics, and at the lowest level, SOP and battle drill
 - Some leaders will ignore or discard learned patterns and either blunder or innovate—the dummy or genius factor

^{*} from Gary Klein, Sources of Power, The MIT Press, 1998, referenced at http://www.cs.mu.oz.au/~ejn/pubs/NorlingHeinze-CogSci00.pdf



What is a template?




- A template is a pattern of activity or things
- It can be compared to the elements of the situational awareness picture at all levels
- A template can be derived from enemy doctrine either published or deduced
- It can be applied piecewise to each datum in the SA picture at that level
- The degree of "fit" of the template to the data can be estimated several ways
- Template evaluation must provide a warning in the case of "too much" as well as "too little"









From FM 100-2-1, The Soviet Army, Operations and Tactics, 16 July 1984. Although the Soviet Union is no more, a lot of people were trained in this way of waging war. In any case, the material is illustrative if not definitive.





Really really elementary example of use of a template

Consider a sensing of a vehicle identified as an armored vehicle.


The sensing is accompanied by a constellation of other sensings. The sensing datum under consideration is examined to see if the other sensings correspond to the old-style Soviet geometric formations: is there another armored vehicle within 100 meters? 400 meters? Is it a tank? An APC or IFV? MTLB? Etc., etc.

If so, is there a command vehicle within 500 meters? A logistic vehicle within 1000 meters? Are the terrain and met conditions favorable for detection if the required vehicles were indeed there, if not sensed?

Is the same sensed set of vehicles present in sensings a day earlier? Two days? Three?

Does the sensing permit recognition of tracks? If so, are there any?

Does the ELINT data base include sensings of the proper type, say R123 radios? And so on.




(from p. 5-11, FM 100-2-1, The Soviet Army, Operations and Tactics, 16 July 1984)



Templating









Simple low level tactical template










Simple low level deception template





Visual signature tank 1—data element being parsed

Visual signature tank 2

Visual signature tank 3

Visual signature tank 4

Acoustic signature—idling

.....etc.

Tracks on ground

Communications

Presence of cmd. Element

Presence of accompanying units

Terrain factors—US access?

Enemy element in overwatch position?

Enemy artillery in range?

Commanding ground nearby?

Increasing terrain restriction?

Easy enemy retreat path?

Disturbed earth along path?

.....etc.



How to estimate congruence or divergence: metrics




- Problem is how to reduce these elements to some numerical value or metric
- Several possibilities
 - ➤ Add up the yeses/noes
 - ➤ Weight the elements and add, normalize, etc.: (Grey System Theory or normal ORSA stuff, take your pick)
 - > Phase space vector manipulation
 - Bayesian Belief Network (BBN)



Total

Simple pseudo-binary approach





Visual signature tank 1	data element being parsed	+1
Visual signature tank 2	not detected	0
Visual signature tank 3	detected 80 meters away	+1
Visual signature tank 4	not detected	0
Acoustic—idling	detected by array	+1
Acoustic—moving	not sensed	0
Chemical signature—exhaust	not sensed, no means to do so	0
Thermal	checked, not present	-1
Radar—conv. cm wavelength	not checked	0
Millimeter wave radar	not checked	0
Lidar	not checked	0
Tracks on ground	UAV checked, not found, ground suitable	-1
Communications	no ELINT	0
Presence of cmd. Element	not sensed, open ground	-1
Presence of accompanying units	not sensed, open ground	-1
Terrain factors—is it suitable?	No	-1

Just add up the yesses (+1s) and contradictions or noes (-1s or 0s), normalize to number of elements (16 in this case)

-2/16: probably not



Simple low level deception template



+1

0

+1

0

+1

+1

+1


+1

0

+1

+1

0



Visual signature tank 1 data element being parsed Visual signature tank 2 not detected Visual signature tank 3 detected 80 meters away Visual signature tank 4 not detected Acoustic signature—idling yes, detected by arrayetc. Tracks on ground UAV checked, tracks found, ground suitable Communications recent xmissions at position Presence of cmd. Element not sensed, open ground Presence of accompanying units not sensed, open ground Terrain factors—US access? Not sensed, cover at positions Enemy element in overwatch position? Enemy artillery in range? Yes Commanding ground nearby? Yes Increasing terrain restriction? Yes Easy enemy retreat path? Yes Disturbed earth along path? Not sensedetc.



Linear deviation metric



- Consider the sum of the values resulting from correspondences of the elements of a template and the elements in a data base, weighted by their judged importance.
- Initially the value of correspondence of the *i*th element may be binary: 0 or 1.
- A refinement might be to include an estimate of the probability of the element in the data base being a true sensing, so that the values might range from 0 to 1, inclusive.
- Normalization allows comparison between templates, which might well have different numbers of potentially evidentiary data elements
- In this case the deviation metric might be

$$F(template\ TRUE) = Congruence = \frac{1}{N} \sum_{i} (weight)*(truth)_{i}$$

Deviation = 1 - Congruence



Phase space deviation metric



- The description of battle has been considered as a vector in an n-dimensional phase space.
- This leads to the possibility of a template being considered a vector in that phase space.
- There are several possible deviation vector measures.
- One is the dot-product of the phase space data elements and the template.
- In this case if the template fit the situational data each element of the template would be accompanied by a datum corresponding to it in the data base. In a first approximation the elements of the presumed detection either correspond to the template or they do not; that is, the confidence in the sensings or the trafficability data or accuracy of the acoustic signature in the situational awareness data base is presumed to be zero or unity.

$$Congruence = \frac{1}{N} \sum_{i} (weight \ of \ template \ element)_{i} (template \ element)_{i} * \frac{(corresponding \ database \ element)_{i}}{(max \ value \ of \ corresponding \ database \ element)_{i}^{2}}$$

Deviation = 1 - Congruence





Bayesian Belief Network (BBN)


- Probability calculation of causes based on observed effects
- Cause → Target of interest, unknown event, etc.
- Effects → Trafficability Data, Acoustic Signatures, etc.
- Probabilities established based on prior information (templates)
- Bayes' Theorem for n basic events, $A_1, A_2, ...A_n$:


$$P(A_1 | B) = \frac{P(A_1)P(B | A_1)}{P(A_1)P(B | A_1) + P(A_2)P(B | A_2) + \dots + P(A_n)P(B | A_n)}$$



Example BBN in Netica










Incongruity detection process







Interesting possibilities



- Deceptive activities and their templates are associated with a characteristic scale or coherence length in space and time
- An agent based approach may be able to access data appropriate to all these scales
- Sparseness of data in local SA data base introduces graininess and hence variation that may mask patterns at lower scales
- Access to multiple scales may compensate for this to some degree
- Insertion of deception or systematic error as an explicit layer may allow training the network by splitting of data set



Problems to solve



- Stech points out that you have to work on at least three levels—obvious, cross, double cross (paraphrase)
- Templates must accommodate this—hard to do, templates become very involved
- Templates of deception must be included—dependent on culture, enemy doctrine, military history
- Templates must change with time, circumstance—this can be accommodated by adding new templates
- Enemy deception doctrine is key



A note on RAID



The Defense Advanced Research Agency (DARPA) is presently developing the Real Time Adversarial Intelligence and Decision Making (RAID) tool.*

- RAID will take three years from contract award to bear fruit.
- The RAID deception module is defensive only.
- RAID is ambitious and hence high risk.
- The deception module will likely be dependent on the rest of the tool, especially the Adversarial Reasoning Model. If any of the whole does not work it risks usability of any component.
- RAID as envisaged in its initial phase will be a tactical level tool only.

* See http://dtsn.darpa.mil/ixo/solicitations/raid/index.htm, accessed 3 January 2005.



Summary




- The opportunity exists to develop a data base tool that may have substantial benefits in lower level operations, including cuing of possible deception
- This tool will take a bottom-up approach to the analysis
- The next step is to:
 - ➤ Choose or devise a simplified surrogate data base,
 - > Devise a set of templates,
 - ➤ Devise and test several metrics for determining fit of the metrics to the data,
 - Estimate the utility of measures of the fit to improve both the commander's and battle staff's interpretation of the situation.




































Methods: Harris Inference from Ambiguities

Process	Description	Modes
Reconstructive Inference	 Detect the presence of spurious signals (sprignals) that are indicators of D&D Apply templates predicted by conjectured preexisting D&D hypotheses: Strong evidence confirming hypothesis A (the simulation), Weak contradictory evidence of hypothesis C (leakage from the adversary's dissimulation effort), Missing evidence that should be present if hypothesis A were true. 	Deduction
Incongruity Testing And Inference	Search for inconsistencies in the data (changes, anomalies, contradictions) Synthesize (conjecture) alternative explanations that attribute the incongruities to D&D (i.e. D&D explains the incongruity of evidence for more than one reality in simultaneous existence) Induce generalizations (as appropriate, when tested and confirmed).	Deduction, then, Abduction, then, Induction

Integrating Methods and Tools to Counter Deception

© Ed Waltz 2005

Page 29







Methods: Whaley-Busby Incongruities

Incongruities about Sprignals and leaks "The possibility of detecting Why that? there? - incongruous with deception, is inherent in the now? only that? everything else effort to deceive. Every What is missing? revealed deception operation necessarily leaves at least two clues: Reveal Conceal · Rev al limited true, incongruities about what but limit exposure Create false impression by is hidden; and structure of truth revealed incongruities about what is displayed in it's Employ physical and stead. prevent exposure of the simulations and misdirection The analyst requires only the appropriate sensors and mindset (cognitive hypotheses) to Incongruities about Incongruities about detect and understand the displayed what is protected meaning of these clues." imperfections and and what should be (Whaley-Busby p. 191). incompleteness protected

Integrating Methods and Tools to Counter Deception

© Ed Waltz 2005

Page 32

Courtesy Frank Stech, MITRE, from Mr. Waltz's tutorial, used with permission





Example

- 1% of a country's inhabitants are infected with a disease:
 - Let A_1 = infected population \rightarrow $P(A_1) = 0.01$
 - Let A_2 = uninfected population → $P(A_2) = 0.99$
- An imperfect diagnostic test has been developed:
 - Let B = a test confirming infection \rightarrow P(B|A₁) = 0.97 and P(B|A₂) = 0.05

•
$$P(A1|B) = \frac{P(A_1)P(B|A_1)}{P(A_1)P(B|A_1) + P(A_2)P(B|A_2)}$$


•
$$P(A1|B) = \frac{(0.01)(0.97)}{(0.01)(0.97) + (0.99)(0.05)}$$

• P(A1|B) = 0.16





Bayesian Belief Network (BBN)



$$P(x) = \sum P(x \mid y_1, y_2,...y_n) P(y_1) P(y_2) ... P(y_n)$$